



UL
LISTED
WIRE CONNECTOR
71 BA

- The color coded barrel provides the proper die number and color.
- The tongue is clearly marked with wire size and die index for CEMBRE tools.

- ## INSTALLATION INSTRUCTIONS

- 1) Select proper "CL" lug for the wire size used.
- 2) Strip the cable insulation for a length equal to that of the connector barrel.
- 3) Insert conductor into the barrel.
- 4) Select the proper die as indicated in the table below.
- 5) Apply the proper # of crimps, as indicated in the same table, starting from the tongue side of the lug.

CATALOG NUMBER		BOLT SIZE	CONDUCTOR		COLOR CODE	INSTALLATION TOOLING		DIE INDEX
			CODE	NAVY		DIE # (# OF CRIMPS)		
						6 sh tons (●)	14.6 sh tons (◆)	
CL8-10	CL8IH-10	# 10	# 8 AWG # 8 WELD # 6 SOL	23	RED	MY2-50 (2)	MY2-C (2)	2
CL8-14	CL8IH-14	1/4						
CL8-516	CL8IH-516	5/16						
CL8-38	CL8IH-38	3/8						
CL8-12	CL8IH-12	1/2						
CL6-10	CL6IH-10	# 10	# 6 AWG		BLUE	MY3-50 (2)	MY3-C (2)	3
CL6-14	CL6IH-14	1/4						
CL6-516	CL6IH-516	5/16						
CL6-38	CL6IH-38	3/8						
CL6-12	CL6IH-12	1/2						
CL4-10	CL4IH-10	# 10	# 4 AWG	40	GRAY	MY4-50 (2)	MY4-C (2)	4
CL4-14	CL4IH-14	1/4						
CL4-516	CL4IH-516	5/16						
CL4-38	CL4IH-38	3/8						
CL4-12	CL4IH-12	1/2						
CL3-10	CL3IH-10	# 10	# 3 STR # 2 SOL	50	WHITE	MY5-50 (2)	MY5-C (2)	5
CL3-14	CL3IH-14	1/4						
CL3-516	CL3IH-516	5/16						
CL3-38	CL3IH-38	3/8						
CL3-12	CL3IH-12	1/2						
CL2-10	CL2IH-10	# 10	# 2 STR	60	BROWN	MY6-50 (2)	MY6-C (2)	6
CL2-14	CL2IH-14	1/4						
CL2-516	CL2IH-516	5/16						
CL2-38	CL2IH-38	3/8						
CL2-12	CL2IH-12	1/2						
CL1-10	CL1IH-10	# 10	# 1 AWG	75	GREEN	MY7-50 (2)	MY7-C (2)	7
CL1-14	CL1IH-14	1/4						
CL1-516	CL1IH-516	5/16						
CL1-38	CL1IH-38	3/8						
CL1-12	CL1IH-12	1/2						
CL1/0-10	CL1/0IH-10	# 10	1/0 AWG	100	PINK	MY10-50 (4)	MY10-C (2)	10
CL1/0-14	CL1/0IH-14	1/4						
CL1/0-516	CL1/0IH-516	5/16						
CL1/0-38	CL1/0IH-38	3/8						
CL1/0-12	CL1/0IH-12	1/2						
CL1/0-916	CL1/0IH-916	9/16						
CL1/0-58	CL1/0IH-58	5/8						

CATALOG NUMBER		BOLT SIZE	CONDUCTOR		COLOR CODE	INSTALLATION TOOLING		DIE INDEX
			CODE	NAVY		DIE # (# OF CRIMPS)		
						6 sh tons (●)	14.6 sh tons (◆)	
CL2/0-14	CL2/0IH-14	1/4	2/0 AWG	125	BLACK	MY14-50 (4)	MY14-C (2)	14
CL2/0-516	CL2/0IH-516	5/16						
CL2/0-38	CL2/0IH-38	3/8						
CL2/0-12	CL2/0IH-12	1/2						
CL2/0-916	CL2/0IH-916	9/16						
CL2/0-58	CL2/0IH-58	5/8						
CL2/0-34	CL2/0IH-34	3/4	3/0 AWG	150	ORANGE	MY16-50 (4)	MY16-C (2)	16
CL3/0-14	CL3/0IH-14	1/4						
CL3/0-516	CL3/0IH-516	5/16						
CL3/0-38	CL3/0IH-38	3/8						
CL3/0-12	CL3/0IH-12	1/2						
CL3/0-916	CL3/0IH-916	9/16						
CL3/0-58	CL3/0IH-58	5/8	4/0 AWG	200	PURPLE	MY19-50 (4)	MY19-C (2)	19
CL3/0-34	CL3/0IH-34	3/4						
CL4/0-14	CL4/0IH-14	1/4						
CL4/0-516	CL4/0IH-516	5/16						
CL4/0-38	CL4/0IH-38	3/8						
CL4/0-12	CL4/0IH-12	1/2						
CL4/0-916	CL4/0IH-916	9/16	250 MCM	250	YELLOW	MY24-50 (4)	MY24-C (2)	24
CL4/0-58	CL4/0IH-58	5/8						
CL4/0-34	CL4/0IH-34	3/4						
CL250-14	CL250IH-14	1/4						
CL250-516	CL250IH-516	5/16						
CL250-38	CL250IH-38	3/8						
CL250-12	CL250IH-12	1/2	300 MCM	300	WHITE	MY30-50 (4)	MY30-C (4)	30
CL250-916	CL250IH-916	9/16						
CL250-58	CL250IH-58	5/8						
CL250-34	CL250IH-34	3/4						
CL300-516	CL300IH-516	5/16						
CL300-38	CL300IH-38	3/8						
CL300-12	CL300IH-12	1/2	350 MCM	350	RED	MY36-50 (4)	MY36-C (4)	36
CL300-916	CL300IH-916	9/16						
CL300-58	CL300IH-58	5/8						
CL300-34	CL300IH-34	3/4						
CL350-38	CL350IH-38	3/8						
CL350-12	CL350IH-12	1/2						
CL350-916	CL350IH-916	9/16	400 MCM	400	BLUE	MY37-50 (4)	MY37-C (4)	37
CL350-58	CL350IH-58	5/8						
CL350-34	CL350IH-34	3/4						
CL400-38	CL400IH-38	3/8						
CL400-12	CL400IH-12	1/2						
CL400-916	CL400IH-916	9/16						
CL400-58	CL400IH-58	5/8	500 MCM		BROWN	MY48-50 (8)	MY48-C (4)	48
CL400-34	CL400IH-34	3/4						
CL500-38	CL500IH-38	3/8						
CL500-12	CL500IH-12	1/2						
CL500-916	CL500IH-916	9/16						
CL500-58	CL500IH-58	5/8						
CL500-34	CL500IH-34	3/4	600 MCM		GREEN		MY60-C (4)	60
CL600-12	CL600IH-12	1/2						
CL600-916	CL600IH-916	9/16						
CL600-58	CL600IH-58	5/8						
CL600-34	CL600IH-34	3/4						
CL750-12	CL750IH-12	1/2						
CL750-58	CL750IH-58	5/8	750 MCM		BLACK		MY76-C (4)	76
CL750-34	CL750IH-34	3/4						

- HT51 also with suffix L, D, -KV, L-KV; RH50; RHM50; HT61; B600; RH61; B51, B500, B500ND also with suffixes L, -KV, ■, L ■, L ■ -KV; B600C; RH60C
- ◆ HT120 also with suffix -KV; HT131-C also with suffixes U, LN; RHC131 also with suffixes LN, -KV; RHM132; RHU131-C; B135-C, B131-C also with suffixes U, LN, -KV, ■, LN ■, LN ■ -KV; B1350-C, B1300-C also with suffixes U, L, -KV, ■, L ■, L ■ -KV; B1320

Note: Symbol ■ in the tool descriptions could be A, E, J or T suffix; it can be added for commercial purposes only.