

Rittal – The System.

Faster – better – everywhere.



SV 9686.040 Busbar support

State: 29/10/2026 (Source: www.rittal.com/uk-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9686.040 - Busbar support for busbar entry (roof section)

For inserting busbar systems into the roof section.

Features

Model No.	SV 9686.040
Product description	
Material	Duroplastic Fire protection corresponding to UL 94
Colour	Similar to RAL 9005
Supply includes	Assembly parts
To fit busbars	50 x 10
Centre-to-centre spacing of busbars	80 mm
Assembly instruction	For the installation of max. 4 busbars (sub-conductors) per phase Cage nut (M8) 4165.500 is required to attach the busbar support to the enclosure section
Packs of	2 pc(s).
Net weight	3.6 kg
Gross weight	3.76 kg
Customs tariff number	85469010
ETIM 9	EC001166
ECLASS 8.0	27400607
Product description	SV busbar holder, 4-pole, 80 mm, for E-Cu 50 x 10 mm, duroplastic, fire protection in accordance with UL 94-V0

Approvals

Approvals

DNV

Lloyds Register

UL + C-UL (listed)